



FS Management™.

22 range. Technical details.

Function

Swivel and visitor chairs with automatic synchro-adjustment: the seat and backrest automatically tilt to any posture the person adopts. When leaning back, the backrest tension increases proportionately. The person using the chair can infinitely adjust the tension. The front position is lockable by engaging the lever. DIN 4550 compliant gas lift for infinite adjustment of the seat height. Visitor chair (model 220/62, 220/72) with automatic synchro-adjustment, but without front locking position and without infinite height adjustment.

Frame

Die-cast aluminium, bright chrome plated star base. Twin wheel swivel castors with load-dependent braking, made of black polyamide in accordance with DIN EN 12529 as the standard version for carpets; with grey soft polyurethane facing for hard floors. Castors optionally electrically conductive. Black polyamide glides as the standard version for carpets and in black polyurethane for hard floorings. Die-cast aluminium, bright chrome plated swivel arms.

Seat and back

Steel tube frames with a flexible middle section, covered with elastic mesh. Foam upholstery with additional cushioning. Exchangeable cover with wider stitched fluting. Integral foam armrests, leather-covered with stitched seam.

Standards

The FS swivel and visitor chairs comply with DIN EN 1335, ANSI/BIFMA X 5.1 and other international office chair standards. Depending on the version they also fulfil the requirements of categories B or C of the DIN EN 1335 office chair standard.



220/62
 □42 □100 □67 □63
 (□16½" □39⅜"
 □26⅜" □24¾")



220/72
 □42 □116 □67 □63
 (□16½" □45⅝"
 □26⅜" □24¾")



220/82
 □42/52 □100/110 □67 □63
 (□16½"/20½" □39⅜"/43¼"
 □26⅜" □24¾")



220/92
 □42/52 □116/126 □67 □63
 (□16½"/20½" □45⅝"/49⅝"
 □26⅜" □24¾")

Symbols

- Seat height
- Overall height
- Width
- Depth

All dimensions in cm (inches).

Subject to technical change without notice.